

# COEX™ C3000 4K IP Fixed Camera Station

The COEX™ C3000 4K IP Fixed Camera Station has a unique compact and lightweight design developed specifically for hazardous-area applications. C3000 camera stations are designed for both toughness and durability as demanded for operation in the most adverse of environments.



COEX C3000 hazardous-area camera stations operate in the most extreme environments worldwide. Designed for toughness, durability, and certified to perform in ambient temperatures from -55°C to +70°C without compromise, they are ideal for oil and gas, marine, and industrial installations.

This advanced camera station combines 4K video with a 20x optical zoom to deliver high-quality image and detail capture.

Featuring the latest encoding technology (2<sup>nd</sup> generation IP encoder), the camera station is capable of triple-stream H.264 and H.265 encoding for simultaneous live view and recording.

The C3000 4K IP Fixed Camera Station has cybersecurity measures built-in, including encrypted video streaming, HTTPS, and 802.1x protocols.

COEX camera stations are compatible with a variety of VMS platforms through ONVIF Profile S and T compliance.

**Options**

- Integral wiper
- COEX FEWS3 wash systems
- IR lamp\*1


# Specifications

CERTIFICATIONS / RATINGS <sup>5</sup>		[OPTIONS]
ATEX / IECEx / UKCA	ATEX II 2GD, Ex db IIB/IIC Gb; Ex tb IIIC Db; T4 / T5 / T6 EN60079-0, EN60079-1, EN60079-31, IEC60079-0, IEC60079-1, IEC60079-31	
ATEX / IECEx / UKCA Certified Temperature	-55°C to +50°C (T6), +60°C (T5), +70°C (T4)	
CSAus Class / Division	Class I, Div 1, Groups A, B, C, D; Class II, Div I, Groups E, F, G; T4 / T5 / T6	
CSAus Class / Zone	Class I, Zone 1, AEx db IIC Gb; Zone 21, AEx tb IIIC Db; T4 / T5 / T6	
CSAus Standards	FM3600, FM3615, FM3616, UL50, UL50E, UL62368-1, UL60079-0, UL60079-1, UL60079-31	
CSAus Certified Temperature	-55 to +50°C (T6), +55/60°C (T5), +70°C (T4)	
CSA Class / Division	Ex db IIC Gb; Ex tb IIIC Db; Class II, Div 1, Groups E, F, G; Class III, Div 1; T4 / T5 / T6	
CSA Standards	C22.2 No. 0, C22.2 No. 60079-0, C22.2 No. 60079-1, C22.2 No. 60079-31, C22.2 No. 62368-1, IEC60529, C22.2 No. 94.1, C22.2 No. 94.2	
CSA Certified Temperature	-55°C to +50°C (T6), +60°C (T5), +70°C (T4)	
EMC	EN61000-6-2, EN 61000-6-4 Class A limits	
EMC (US & Can.)	FCC CFR47 Part 15 Class A ICES-003 Class A	
CE / UKCA	IEC62368-1, IEC60825-1	
DNV	TAA00001M2	
INMETRO	BRA 21.GE0018X	
ENVIRONMENTAL		
Operating Temperature	-45°C to +70°C / -49°F to +158°F	
Storage Temperature	-45°C to +80°C / -49°F to +176°F	
Ingress Protection	IP66 & IP68 (30m Submersion for 4 hrs) to IEC60529 Type 6 Enclosure	
Salt Mist	IEC60068-2-52 & IEC60945 Section 8.12	
Vibration	0.7 g to IEC60068-2-6 & IEC60945	
Wind Loading	Operational to 130 km/h, survival to 268 km/h	
MECHANICAL		
Material	Electro-polished 316L stainless steel	
Window	4K grade toughened glass, thermostatically operated demister [Wiper <sup>2</sup> ]	
Mounting Orientation	Upright or inverted	
Mounting Base	1 x Ø 12.5 mm / 0.49" fixing hole	
Dimensions <sup>*1</sup> (W x D x H)	179 x 310 x 235 mm / 7.05" x 12.21" x 9.25"	
Weight <sup>*1</sup>	8 kg / 17.6 lb	
Cable Gland Entries	1 x M20	
ELECTRICAL		
Input Power Options	24 V AC/DC (±10%) 50/60 Hz	
Power Consumption <sup>*1</sup>	8 VA Quiescent 11 VA Operating 24 VA Operating (with heater) 27 VA Max	
Wash Control <sup>*1</sup>	Volt free switched output (24 V 0.75 A max)	
Auxiliary Inputs <sup>*3</sup>	1 x contact closure input (5 V pull up) [up to 4 available on request]	
Relay Outputs <sup>*3</sup>	1 x volt free switched output (24 V 0.75 A max) [up to 2 available on request]	
Audio <sup>*3</sup>	[Line Input]	
CAMERA OPERATION		
Preset Memory	128 user programmable preset positions (zoom, focus)	
Wash/Wipe <sup>*1</sup>	[Optional wash/wipe with auto-wiper off]	
ONVIF Control Features	Zoom and focus control, preset store/recall, auxiliary controls (wash/wipe/lamps/auto focus), wash/wipe and lamps control mappable to ONVIF presets for control systems that have no support for auxiliary commands, alarm inputs, and relay outputs	
IR Lamp Control <sup>*1</sup>	Manual/auto control of a connected IR lamp	
IR Focus Compensation <sup>*1</sup>	Manual/auto control of IR focus compensation and automatic compensation of focus preset positions	

DAY/NIGHT CAMERA / LENS	
Image Sensor	1/2.5 Exmor-R CMOS sensor
Signal System	4K 2160p 25/29.97 FPS FHD 1080p 25/29.97/50/59.94 FPS
Effective Pixels	8.51 mega pixels
Zoom Range	20x zoom (up to 240x with digital zoom)
Focal Length / Aperture	4.4 mm (wide) to 88 mm (tele), F2.0 to F3.8
Angle of View (H)	70.2° (wide) to 4.1° (tele), 60° (wide) to 3.5° (tele) with image stabilizer on
Minimum Illumination (50IRE, ICR OFF)	0.4 lux (1/30 s) 0.06 lux (1/4 s, 1/3 s)
Minimum Illumination (50IRE, ICR ON)	1.6 lux (1/30 s) 0.21 lux (1/4 s, 1/3 s)
Electronic Shutter	Auto (1/1 to 1/10,000 s, 28 steps)
Signal/Noise Ratio	> 50 db (weight on)
Features	Digital zoom on/off, auto/manual focus, auto/manual iris, auto/manual IR cut filter remove (ICR), auto exposure (AE), automatic gain control (AGC), auto white balance (AWB), backlight compensation (BLC), auto slow shutter, visibility enhancer (VE), defog, highlight compensation (HLC), Noise Reduction (NR)
Image Stabilization	EIS
VIDEO ENCODING	
Compression Standards	H.264 (MPEG4 part 10/AVC) high, main, base profiles H.265 (MPEG-H part 2/HEVC), MJPEG
Bitrate Mode	Constant Bitrate (CBR), Variable Bitrate (VBR)
Encoding Capability	Up to 3 independently configurable encoded video streams
Stream Bitrate <sup>*4</sup>	100 kb/s to 25 Mb/s
Image Resolution <sup>*4</sup>	4K (3840 x 2160), Full HD 1080p (1920 x 1080), 720p (1280 x 720), D1 (720 x 576/480), 4CIF (704 x 576), CIF (352 x 288)
Image Rate <sup>*4</sup>	HD (up to 60 IPS), 4K (up to 30 IPS)
GOP Structure	I-frame only, 5 to 240 frames
Region of Interest (ROI)	Configurable per encoded video stream, ability to crop a selected area of the image source for encoding (variable resolution and aspect ratio)
AUDIO ENCODING	
Compression Standards	ARM AACLC, ARM AACLC MPEG2, ARM AACHE, ARM AACHE V2
Sample Rate	48 kHz, 44.1 kHz, 32 kHz, 16 kHz
Stream Bitrate	12 to 384 kb/s (AACHE and AACHE V2 32 to 64 kb/s)
NETWORK DEVICE	
Interface Options	Ethernet (100Base-T, 10-Base-T), Auto/full/half duplex, Auto/10/100, Configurable MTU Size
Protocols	TCP/IP, UDP, ICMP, DHCP, DNS, HTTP, HTTPS, NTP, RTSP/RTP/RTCP, TSRTSP, RTMP, RTMPS, SRT, IGMP, SNMP, SYNS, SSL, TLS, 802.1x (EAP)
Control Protocol	SYNS, ONVIF (Profile S, T compliant)
Video Stream Delivery	RTSP/RTP (Unicast: UDP/TCP, Multicast UDP), TSRTSP, RTMP, RTMPS, SRT
Network Discovery	SYNS, WS-Discovery (ONVIF)
Device Security	Multiple users and 7 access levels protecting access to the web interface, ONVIF and RTSP services, HTTPS support, HTTP disable, 802.1x (EAP), video streaming disabled until change of default password, unicast stream disable
Supported Internet Browsers	Chrome/Firefox/IE/Edge (No Active-X browser components required)
System Maintenance	Field upgradeable firmware, diagnostic logs Hardware system supervisor providing temperature management, cold-start, auto-shutdown and watchdog control

NOTE: \*1 Dependent on certification and equipment fitted. \*2 Wipers are consumable items that need regular replacement. Please refer to the manual for recommendations and maintenance. \*3 Dependent on cable tail option. \*4 Maximum permissible resolution, bitrate and framerate per additional stream will be reduced dependent on the configuration of the primary stream. \*5 Exact certification requirements must be specified at the time of order.

## PART CODE STRUCTURE

C3 - A B C D - E - F G H J

(Example) C3 - 1 F 85 - W - E 5 E X

**A - CAMERA HOUSING SIZE**

1 Size 1 camera housing

**B - FIXED/PTZ**

F Fixed

**C - DAY/NIGHT CAMERA**

85 4K UHD, 20x zoom

**D - THERMAL IMAGING MODULE**

N/A

**E - WIPER**

Without wiper

**J - SPECIAL**

Standard build

X Special build

**H - OUTPUT TRANSMISSION TYPE**

E Ethernet Base-T

**G - BASE/MOUNTING TYPE**

Standard fixed mounting

5 Alternative fixed mounting

**F - TECHNOLOGY SERIES**

E 2nd Gen, IP encoder